



Go further

with rotating table machine !

1. Fully automated rotary table.
6, 8, 12, divided table available.
2. Self detection of goods existence.
Machine has a reliably detect system of the presence of the object.
3. Two place stitch is possible.
When stitch a wide object such as brief it is able to stitch two positions of the object.
4. Compact design.
5. Simple operation.
It is easy only put the object on the table-clamp.
6. Body machine is same as SK9-155, machine works for a long period with stable condition.

Model

SK9-155R

WORK SAMPLE

仕上り見本



Specifications


SK9-155		SK9-155R			
Stitch speed	1.5-1.8 sec	Table diameter	600 mm		
Presser foot height	28 mm	Nos. of station	6	8	12
Needle used	TVx5, DPx5	Table size	900 x 750 mm		
Thread size	#30-80 Cotton	Table height	800 mm		
Table size	W900xD750mm	Stitch width	10 mm		
Stitch width	10 mm	Nos. of stitch	1 or 2 position		
Throat depth	210 mm	Stitch space	35 - 90 mm	35 - 60 mm	35 - 40 mm
Start	Pedal	Stitch speed	Abt. 1.5 - 1.8 sec.		
Emergency stop	Pedal	Rotating time	2 - 2.3 sec	1.5 - 1.8 sec	1 - 1.2 sec.
Stop	Automatic stop	Stitch yarn remain	7 or 25 mm from the knot		
Work heights	800 mm	Throat depth	90 mm		
Power input	100 V 50/60Hz	Needle used	TV x 5, DP x 5		
Weight	Abt 118 Kgs.	Thread	#30 - 80 cotton		
		Detector	Beam sensor		
		Control	Manual / Automatic 1 / Automatic 2		

Manufactured by

Sales

QUEEN LIGHT ELECTRONIC INDUSTRIES LIMITED

576-1 Minato, Wakayama, Japan 640-8404
 Phone 8173-431-6245 Fax 8173-433-8815
 E-Mail: info@queenlight.co.jp
 Web site: www.queenlight.co.jp



External advancement on Sealing & Stitching Machine Field

QUEEN LIGHT Brand

Industrial Sewing machine



Model
SK9-155

Model

SK9-155

Advanced Auto-Fasten Stitcher

This machine was developed for the purpose to tug or tie off
GLOVES / SOCKS
GARMENTS
UNDERWEARS / Etc.

To make one piece or to Attach labels on above products, and have no parallel on this field.

It provides

Safety

Reliable

Efficiency

Label attach work or tie-off work with quite NO SKILL is required.

FEATURES

HIGH EFFICIENCY THREAD CUTTER

Automatic thread cutter cuts binding yarn at every time after binding, Hence quality of cutter material was investigated minutely, it cuts cleanly for a long period

EASY SIMPLY TO USE

Only step ON the foot pedal for machine start. It is very easy and simply operation.

TROUBLE FREE

Due to CAM drive system, machine has very few troubles in long time use.

STABLE STITCH CONDITION

Stitch condition is always stable of which is using accurate finished parts and carefully fabrication.

MATERIAL DAMAGE

Due to binding with yarn, machine brings on very few chance to damages materials.

NO WORRY FOR INJURY

No pins and staples are used, customers are free of concern to dispose pins or staples.

TAG ATTACHING

Tag attaching is also possible with this machine.

NO SPECIAL WORK SPACE IS REQUIRES

Machine has caster, it is easy to move therefore any place is possible to operate this machine.

NEEDLES TO BE USED

Thick to thin needle can be attached in this machine, customer have the option of suitable needle selection.

Sub Class "K" Model
is also available for binding
KNITTED Materials.